

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000093

International filing date: 11 January 2005 (11.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0401998.0
Filing date: 30 January 2004 (30.01.2004)

Date of receipt at the International Bureau: 17 February 2005 (17.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/GB 2005 / 0 0 0 0 9 3



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.


In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 24 January 2005



Patents Form 1/77

Patents Act 1977
(Rule 16)**The
Patent
Office**THE PATENT OFFICE
RM

30 JAN 2004

RECEIVED BY FAX

1/77

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH**Request for grant of a patent**(See the notes on the back of this form. You can also get
an explanatory leaflet from the Patent Office to help
you fill in this form)

1.	Your reference	P900GB00/TYCO		
		02FEB04 E849452-2 002902 PG1/7750 0.00-0401998.0 ACCOUNT CHA		
2.	Patent application number (The Patent Office will fill in)	0401998.0		30 JAN 2004
3.	Full name, address and postcode of the or of each applicant (<u>underline all surnames</u>)	Tyco Electronics Raychem NV Diestsesteenweg 692 B-3010 Kessel-10		
	Patents ADP number (if you know it)			
	If the applicant is a corporate body, give the country/state of its incorporation	Belgium 8360711001		
4.	Title of the invention	OPTICAL DEVICE		
5.	Name of your agent (if you have one)	K.R. Bryer & Co.		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	7 Gay Street Bath BA1 2PH		
	Patents ADP number (if you know it)	Anthony William Jay Tyco Electronics UK Ltd European Patent Department Faraday Road, Dorcan, Swindon, Wiltshire SN3 5HH 10777002 23655002		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES		

Patents Form 1/77

30-JAN-2004 17:00 FROM K R BRYER AND CO

TO 01633814444

P.04/22

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 10

Claim(s) 4

Abstract 1

Drawing(s) 1

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

ONE

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

30.01.04

12. Name and daytime telephone number of person to contact in the United Kingdom

G J WHITFIELD
(01225 428877)**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

0093237/30 Jan 04 03:45

1.

OPTICAL DEVICE

The present invention relates to an optical device for
5 containing an optical component, and particularly an
optical device for containing a butt ended optical
component. The present invention also relates to a
method of sealably enclosing an optical component, and in
particular a butt ended optical component.

10

It is well known that moisture has adverse effects on the
properties of optical components. The split ratio of
optical splitters, for example, may be influenced by the
presence of moisture, and in optical connectors moisture
15 may lead to increased losses. In order to overcome this
problem, it is well known to provide optical components
in sealed packages in order to protect the optical
components against the damaging effects of moisture and
other environmental influences.

20

However, provision of optical components in sealed
packages often results in compromised optical performance
caused by stress in the optical fibres due to temperature
variations which cause expansion and contraction of the
25 packaging material and/or variations in the pressure of
the atmosphere within the sealed package. In prior art
packages, such as the one described in the Applicant's

earlier International Patent Application No. 2
PCT/GB03/0059, or the one shown in cross-section in
figure 1, the fibres 40, 50 are arranged such that the
optical component 30 is held in a fixed position within
5 the enclosure 20 with the consequence that, for example,
any expansion or contraction of the optical fibres 40, 50
under variations in environmental conditions, such as
extreme temperature variations, will result in stress
through the fibres 40, 50 thereby causing a loss of
10 optical performance.

There is therefore a requirement for an optical device
which addresses the problems of the prior art by avoiding
stress through the optical fibres and the consequential
15 loss in optical performance under variations in
environmental conditions such as, for example, variations
in temperature or humidity.

Accordingly, a first aspect of the present invention
20 provides an optical device comprising an enclosure having
a wall member defining a cavity and a sealable fibre
entry portion, an optical component located within the
cavity, and at least two optical fibres connected to the
optical component and extending, substantially adjacent
25 one another, through the entry portion.

As the optical fibres extend through the entry portion

3

substantially adjacent one another, the optical component is held inside the enclosure in a sealed environment, thereby protected from the effects of variations in environmental conditions such as humidity. As the optical component is held in position relative to the enclosure at only one side of the component, the component is effectively free to move within the enclosure in the event that environmental conditions such as variations in temperature, cause the expansion or contraction of the optical fibres and/or other packaging elements. Thus, expansion or contraction of the fibres and/or other packaging elements is possible without stress to the fibres, as would be experienced using prior art devices. By avoiding stress in the optical fibres, the loss in optical performance that is experienced using prior art devices, is avoided.

This invention is particularly, but not exclusively directed to optical devices comprising one or more butt ended optical components. A butt ended optical component is an optical component in which the optical fibre connections are located on one side of the component.

The optical component may comprise any passive component, such as, for example, a planar splitter, filter wavelength division multiplexer (FWDM), arrayed wavelength grating (AWG), isolator, filter and the like.

4

It will be appreciated by the skilled person that these are merely examples of suitable passive components and that any other suitable passive component known to the skilled person may be located within the cavity. It will
5 also be readily understood by the skilled person that the optical component may be any suitable active component available to the skilled person and may be used as an alternative or in addition to a passive component within the cavity of the optical device.

10

Preferably, the optical fibres provide incoming and outgoing fibres for the optical device.

Preferably, the fibre entry portion is arranged to
15 receive the fibres substantially side by side as they extend through the entry portion. This allows for a better seal of the enclosure around the optical fibres if the fibres are arranged side by side, rather than being arranged such, for example, they cross over one another.

20 More preferably, the fibres are arranged substantially parallel to one another as they extend through the fibre entry portion.

The enclosure is preferably substantially flexible,
25 although it may alternatively be substantially rigid or at least a portion of the enclosure may be flexible while another portion of the enclosure may be rigid.

Preferably, the optical device further comprises temperature control means. By providing temperature control means, a reduction in the possibility of condensation within the device may be achieved, while in addition, excessively high and/or low temperatures may also be avoided.

The temperature control means is preferably provided in any suitable location such as within the wall member of the enclosure, or within the cavity of the enclosure.

The temperature control means may comprise a heat sink or heat pipe, and/or an active temperature controller such as a heater, for example an electrical heater and/or an active cooling element.

Alternatively, or in addition, humidity control means, such as a desiccant, may be provided to further reduce the possibility of condensation within the enclosure.

The enclosure may comprise an insulating layer. Preferably such an insulating layer is located on an interior surface of the wall member.

In a preferred embodiment, the enclosure comprises a laminar material. More preferably, the laminar material

6

comprises a moisture resistant layer. The moisture resistant layer provides a substantially moisture resistant enclosure for surrounding the optical component. Preferably, the moisture resistant layer
5 comprises a layer of aluminium or any other suitable metal.

Preferably, the optical component is arranged on a support, possibly with other optical components, and the
10 optical fibres routed in accordance with a predetermined circuit configuration with the optical fibre ends fed through the entry portion for optical connection with other components. This allows for prefabrication of the optical component and optical fibres, thereby allowing
15 for automation of the circuit assembly, and quick and simple installation of the optical component and optical fibres within the enclosure to provide an optical device according to the present invention.

20 The optical device may contain a single optical component located within the cavity defined by the wall member or alternatively, more than one optical component may be located within the cavity, with at least two optical fibres connected to each optical component and extending,
25 substantially adjacent one another, through the entry portion.

7

A further aspect of the present invention provides a method of sealingly enclosing an optical component, the method comprising the steps of:

- 5 - providing an enclosure having a wall member defining a cavity and a sealable fibre entry portion;
- arranging an optical component connected to at least two optical fibres within the cavity such that the two optical fibres extend, substantially adjacent one another, through the entry portion; and
- 10 - sealing the fibre entry portion so as to sealably retain the optical component within the cavity.

This provides an optical device in which the optical component or components are held in a 'free floating' arrangement within the cavity such that, under variations in environmental conditions, such as extreme temperature variations where expansion/contraction of the fibres and/or other packaging elements may occur, stress through the optical fibres and consequential optical loss is

20 avoided.

Preferably, the method further comprises the step of providing a polymer strip adjacent the optical fibres at the entry portion prior to sealing the entry portion. On

25 sealing of the fibre entry portion, the polymer strip then seals around the optical fibres, thereby sealing any

30-JAN-2004 17:02 FROM K R BRYER AND CO

TO 01633814444

P.13/22

8
gaps between the fibres and the wall member and providing
an improved seal at the fibre entry portion.

The fibre entry portion may be sealed using heat and/or
5 pressure applied at the fibre entry portion until the
desired seal is achieved.

The present invention further provides a kit-of-parts for
forming a device as defined above.

10

An embodiment of the present invention will now be
described, by way of example only, and with reference to
the following figures 2 to 4, in which:

Figure 2 is a perspective view of a butt ended
15 optical component;

Figure 3 is a perspective view of an enclosure
according to an embodiment of the present invention; and

Figure 4 is a cross sectional view of the embodiment
of figure 3.

20

Figure 2 shows a butt ended optical component 30 with an
incoming optical fibre 40 and an outgoing optical fibre
50, the incoming optical fibre 40 and the outgoing
optical fibre 50 both arranged on the same side of the
25 optical component 30, in a so-called butt ended
arrangement. Such an optical component is shown in
figures 2 and 3 as part of an embodiment of an optical

9

device according to the present invention.

Figures 3 and 4 show an optical device 10 according to the present invention comprising an enclosure 20 defining a sealable fibre entry portion in which an optical component 30 is contained. The enclosure 20 is sealed around the incoming and outgoing optical fibres 40 and 50 of optical component 30 such that the optical component 30 is held in a 'free floating' arrangement within the enclosure 20. In other words, and as is clearly shown in the cross sectional view of figure 4, the incoming and outgoing optical fibres 40 and 50 are held substantially adjacent one another at the entry portion 60 when the entry portion 60 is sealed, thereby holding the optical component within the enclosure 20 such that the optical component is anchored at one side only relative to the enclosure. A sealing strip 70 is provided between the fibres 40, 50 and the wall member of the enclosure 20 at the fibre entry portion 60.

20

Thus, in the sealed optical device 10, the optical component 30 is free to move within the enclosure 20 in the event of contraction and/or expansion of the optical fibres 40, 50 and/or other packaging elements, due to variations in environmental conditions such as temperature variations. Therefore, on expansion and/or contraction of the optical fibres 40, 50 and/or other

30-JAN-2004 17:03 FROM K R BRYER AND CO

TO 01633814444

P.15/22

10

packaging elements, the optical component 30 is free to move within the enclosure 20, thereby avoiding stress on the fibres 40, 50 as would occur if the optical component 30 was not free to move, but instead was rigidly held within the enclosure 20, as is the case in prior art optical devices. By preventing stress on the optical fibres, optical quality is maintained and optical losses avoided.

10 Although aspects of the invention have been described with reference to the embodiment shown in the accompanying drawings, it is to be understood that the invention is not limited to the precise embodiment shown and that various changes and modifications may be effected without further inventive skill and effort. For example, the enclosure may accommodate more than one optical component, and may define one or more sealable fibre entry portions, provided each optical component is held in a 'free-floating' arrangement relative to the enclosure, as described above.

CLAIMS

- 5 1. An optical device comprising an enclosure having a wall member defining a cavity and a sealable fibre entry portion, an optical component located within the cavity and at least two optical fibres connected to the optical component and extending, substantially adjacent one another, through the entry portion.
- 10 2. An optical device according to Claim 1 wherein the optical fibres provide an incoming and outgoing fibre for the optical component.
- 15 3. An optical device according to Claim 1 or Claim 2 wherein the fibre entry portion is arranged to receive the at least two fibres substantially side-by-side as they extend through the entry portion.
- 20 4. An optical device according to Claim 3 wherein the optical fibres are arranged substantially parallel to one another as they extend through the entry portion.
- 25 5. An optical device according to any preceding Claim wherein at least a portion of the enclosure is flexible.

12

6. An optical device according to any preceding Claim further comprising temperature control means.

5 7. An optical device according to any preceding Claim wherein the enclosure comprises a laminate.

8. An optical device according to Claim 7 wherein the laminate comprises a moisture resistant layer.

10

9. An optical device according to Claim 8 wherein the moisture resistant layer comprises aluminium.

15

10. An optical device according to any preceding Claim wherein the enclosure comprises an insulating layer.

20

11. An optical device according to any preceding Claim in which the optical device comprises a plurality of optical components located within the cavity, and at least two optical fibres connected to each optical component and extending, substantially adjacent one another, through the entry portion.

25

12. An optical device according to Claim 11 in which the wall member defines a plurality of fibre entry portions, such that each optical component is

13
associated with a separate fibre entry portion through
which the optical fibres to which each individual
optical component is connected extend through a
separate fibre entry portion to the optical fibres
5 connected to other optical components.

13. An optical device according to any preceding
Claim wherein the enclosure is of a size and shape for
fitting into an optical fibre organiser tray.

10

14. A fibre optic organiser tray having an enclosure
according to Claim 13 fitted therein.

15. A method of sealingly enclosing an optical
15 component, the method comprising the steps of:

- providing an enclosure having a wall member defining
a cavity and a sealable fibre entry portion;
- arranging an optical component connected to at least
two optical fibres within the cavity such that the two
20 optical fibres extend, substantially adjacent one
another, through the entry portion; and
- sealing the fibre entry portion so as to sealably
retain the optical component within the cavity.

25 16. A method according to Claim 17 further comprising
the step of providing a polymer strip adjacent the
optical fibres at the entry portion prior to sealing

14

the entry portion.

17. A method according to Claim 17 or Claim 18
wherein the fibre entry portion is sealed using heat
and/or pressure

5

18. Kit of parts for forming an optical device
according to any one of Claims 1 to 13.

10 19. An optical device as hereinbefore described with
reference to the accompanying drawings.

20. A method substantially as hereinbefore described
and with reference to the accompanying drawings.

15

15

ABSTRACT**OPTICAL DEVICE**

5 An optical device comprising an enclosure having a wall
member defining a cavity and a sealable fibre entry
portion, an optical component located within the cavity
and at least two optical fibres connected to the
10 optical component and extending, substantially adjacent
one another, through the entry portion. The invention
also concerns a kit-of-parts for forming such a device,
and a method of sealably enclosing an optical
component.

15

FIG. 4

1/1

